

Guarantee terminal's availability whatever happens

- Assure terminal availability rate if power and network fail
- Make NFC payment a seamless consumer experience
- Robust and functional to meet merchants' daily needs



THE MOVE/2500 OFFERS
A SEAMLESS PAYMENT
EXPERIENCE. A POCKET-SIZED
PORTABLE TERMINAL, IT COMPLIES
WITH FUTURE SECURITY
STANDARDS.

HIGHEST SECURITY

The Move/2500 is PCI-PTS 5.x certified. Its Telium TETRA OS uses the latest cryptographic schemes with future-proof key length.

ALL PAYMENT OPTIONS

The Move/2500 enables NFC couponing and wallet use cases, in addition to EMV Chip & PIN, swipe and contactlesss.

DESIGNED FOR MOBILITY

Designed for indoor and outdoor use, the Move/2500 Portable is a pocket-size and offers extended battery. It is the perfect business companion for merchants.





GUARANTEED TERMINAL AVAILABILITY

In a single terminal, the Move/2500 Hybrid comes with wired communication capabilities (Ethernet, PSTN) or wireless (4G,3G, GPRS, Dual SIM) or WiFi. Then it guarantees terminal payment acceptance availability in case of network failures.

SEAMLESS NFC PAYMENT

The Move/2500 boosts contactless payment by offering customers a seamless experience through a dedicated card-reader zone and faster transaction flow.

SECURE TELIUM TETRA OS

Backed by 40 years of experience and with its user-friendly interface, the Telium TETRA operating system includes the best security mechanisms embedded to protect transaction privacy and leverages Ingenico's unique portfolio of payment applications.

COMPATIBLE WITH INGENICO'S SUITE OF SERVICES

Keeping the solutions connected, the Move/2500 works in unison with Ingenico's supporting service platforms, meaning merchants will have access to business services such as back office reporting and e-receipt management. Software updates and day-to-day support deliver a hassle-free experience.





| Processor | Application & Cryptoprocessor | • Cortex A5 | • | • |
|-------------|---|--|--------|--------|
| Memory | | • 256MBFlash,128MBRAM • 512MBFlash,128MBRAM | Option | Option |
| os | | •Telium TETRA | • | • |
| SIM | | •2 SIM | Option | Option |
| SAM | | • 2 SAM • 3rdSAM | Option | Option |
| Cardreaders | Magstripe Smart card NFC/Contactless | ISO 1/2/3,500KlifespanEMVLevel1,500KlifespanEMVLevel1compliant | • | • |
| Display | • Colour | •2.4"backlit,QVGA (320x240pixels) | • | • |
| Keypad | | 16keys, raisedmarking,backlit4 FunctionalKeyswithout backlight | • | • |
| Audio | • Buzzer | | • | • |

^{*}Depending countries

| | | | 2500 HYBRID | 2500 PORT. |
|-----------------------|--|---|----------------------|-----------------------|
| ThermalPrinter | Speedinlines/s Paperrollcage | upto24lines/s58mmwidthxØ40mm | • | • |
| Terminal connectivity | • WAN • LAN • Wired | 4G* (fallbackGPRSonly)or/ and3Gand/orGPRS•WiFi Dial-upModemRJ45 Ethernet 10/100 baseTRJ45 | Option Option Option | Option Option N/A N/A |
| Terminal connections | USBSerialPower Supply | MicroUSBHost&SlaveRS232RJ11Dedicatedpowerjack | • | N/A |
| Battery | • Li-ion | •2200mAh | • | • |
| Terminalsize | PortableHybrid | •168x81x58 mm (6.6x3.2x2.3") •168x81x69 mm (6.6x3.2x2.7") | N/A | • N/A |
| Weight | • Terminal + Battery | • 320g(11oz) | • | • |
| Environment | Operating Temperature Storage Temperature Operating Humidity | -10°C to +40°C (14°Fto104°F) -20°Cto+55°C (-4°Fto131°F) 85% non-condensing at+40°C(104°F) | • | • |
| Security | | • PCIPTS5.x &4.xonline &offlinecertified | • | • |

MOVE/

MOVE/



CONTACT

FOR QUESTIONS, PLEASE CONTACT

ALHAMRANI UNIVERSAL COMPANY P.O. BOX 1229 JEDDAH 21431 KINGDOM OF SAUDI ARABIA

TEL: +966 12 606 5555 FAX: +966 12 606 2036

AU-SALES@UNIVERSAL.COM.SA AU-INFO@UNIVERSAL.COM.SA